



TECHNICAL DRAWING



HOW TO ORDER

Model	Cover type	Lenght
SLOT-FR	LWH	
SLOT-FR Slot-FR	LWH with opal cover	050 up to 50 cm 100 over 50 to 100 cm 150 over 100 to 150 cm 200 over 150 to 200 cm 250 over 200 to 250 cm 300 over 250 to 300 cm



With opal cover

Order code example: **SLOT-FR-LWH200**

Note: cable feeding to be made during installation.

SLOT-FR

APPLICATIONS

Slot-FR profile has been designed to realize complex polygonal light geometries to be integrated into plasterboard ceilings and walls. Through the use of the dedicated mounting kit with different gradient from 30° to 180°, it is possible to joint and pre-assemble several elements to create endless configurations of the lighted element.



FEATURES

Trimless element
Easy mounting on plasterboard
Light emission width of only 11mm

SPECIFICATIONS

Physical

Body material	Aluminium
Body finish	Anodization
Screen material	PMMA
Protection rating	IP20
Weight	0,25 Kg/m
Mounting	Trimless on plasterboard

ACCESSORIES

Mounting kit and potting options

30° junction kit	CMP01161
45° junction kit	CMP01162
60° junction kit	CMP01163
90° junction kit	CMP01164
120° junction kit	CMP01165
180° junction kit	CMP01166